

The market requires even more powerful **special equipment** in the future based on **individual problem solutions**.  
 We want to meet these requirements using our expertise in combination with our core competences and the Baka efficiency in collaboration with our capable partners.



Wir bauen Stapler nach Maß

**mehr als 50.000 Sondergeräte**

... über 300 auf

[www.bAKA.de](http://www.bAKA.de)

**References:**

Aleris, Aluplast, Audi, BMW, Bosch, Continental, Corovin, Daimler, Dethleffs Wohnmobile, Deutsche Bundeswehr, Deutz, EADS, EvoBus, Fiege-Engineering, Gaerner, Grässlin, Habisreutinger, Handtmann-Armaturen, Heidelberger-Druck, Hilti, Hoechst, Hörmann Türen, Hüller Hille, INA Schaeffler, ISE Industries, Kaiser + Kraft, Kärcher, Knauf Gips, König & Bauer, Krauss-Maffei, Loher Raumexklusiv, Mahle, MAN, Mercedes Benz Gebrauchtteile-Center, Metabo, MTU, Neumag, Niehoff, nkt cables, Peugeot, Porsche, Renault, Schefenacker, Siemens, Stahl, Viessmann, Volkswagen, Windhoff, ZF

Presented by:



**D. Bader Söhne GmbH & Co. KG · Germany**

Rathausstraße 37 · D-73630 Remshalden  
 Postfach 1320 · D-73626 Remshalden  
 Telefon: +49 (0)7151/7006-0  
 Telefax: +49 (0)7151/7006-50  
 E-mail: [Verkauf@baka.de](mailto:Verkauf@baka.de) · Internet: [www.baka.de](http://www.baka.de)

2009/08 Quick Overview Electric pedestrian lift truck with attachment



Electric pedestrian lift truck  
 with attachment

**We build customised forklifts**



SO E 29184, EGV 1010 SO, for tilting switching cabinets, hydraulic tilting 90°, Load capacity 500 kg, Fork length 1000 mm



SO E 29749, EGV 1000-16, with customised holder for hospital beds, load carrier rotatable 45° left and right, Load capacity 180 kg



SO E 30129, EGV 0,2 SO, with attached tensioning and rotating clamp 90° rotate right, Load capacity 200 kg, lifting height centre clamping jaws 600-1500 mm, Gripper opening for Ø 356 mm



SO E 30243, EGV 2000-20, with 360° rotator Load capacity 2300 kg at load centre distance 650 mm, Lift height 2000 mm, Fork length 1200 mm



SO E 29747, EGV 1000-29, with 360° rotator, Load capacity 350 kg at load centre distance 625 mm, Lift height 50-2770 mm, solid slider fork, Fork length 1150 mm



SO E 30423-24, EGV 1000-16, with lifting slides pivotable 30° on one side, Load capacity 1000 kg at load centre distance 600 mm, Lift height 90-1400 mm, Fork length 1150 mm



SO E 28290, EGV SO, with attached tilting and lifting platform, Load capacity 1000 kg, Platform size 1800x1600 mm, Lift height 10-410 mm, tilt angle 90°



SO E 29317, EGV 4000 SO, FEM fork holder, Solid fork, fork tilt, 0-5° upwards, Load capacity 3200 kg, Lift height 190-3390 mm, Fork length 900 mm, with hydraulic tensioning for holding tools



SO E 29296, EGV 2000-SO, Load capacity 1600 kg, dual lift function with 2 separate lifting sledges A Lift height fork 90-1000 mm, Fork length 1650 mm, B lifting height centre clamp 700-2000 mm, clamp opening 400-1600 mm