

The market requires even more powerful **special equipment** in the future based on **individual problem solutions**.
We want to meet these requirements using our expertise in combination with our core competences and the Baka efficiency in collaboration with our capable partners.



Wir bauen Stapler nach Maß

mehr als 50.000 Sondergeräte

... über 300 auf

www.bAKA.de

References:

Aleris, Aluplast, Audi, BMW, Bosch, Continental, Corovin, Daimler, Dethleffs Wohnmobile, Deutsche Bundeswehr, Deutz, EADS, EvoBus, Fiege-Engineering, Gaerner, Grässlin, Habisreutinger, Handtmann-Armaturen, Heidelberger-Druck, Hilti, Hoechst, Hörmann Türen, Hüller Hille, INA Schaeffler, ISE Industries, Kaiser + Kraft, Kärcher, Knauf Gips, König & Bauer, Krauss-Maffei, Loher Raumexklusiv, Mahle, MAN, Mercedes Benz Gebrauchtteile-Center, Metabo, MTU, Neumag, Niehoff, nkt cables, Peugeot, Porsche, Renault, Schefenacker, Siemens, Stahl, Viessmann, Volkswagen, Windhoff, ZF

Presented by:



D. Bader Söhne GmbH & Co. KG · Germany

Rathausstraße 37 · D-73630 Remshalden
Postfach 1320 · D-73626 Remshalden
Telefon: +49 (0)7151/7006-0
Telefax: +49 (0)7151/7006-50
E-mail: Verkauf@baka.de · Internet: www.baka.de

2009/08 Quick Overview ATEX-Equipment



Equipment in ATEX design
for use in areas at risk
of explosion

We build customised forklifts



SO HU 58732-34, hand lever jack lift , Load capacity 2000 kg, Stainless steel design, for zone 1, cat. 2G, ex-group IIA, T4



SO M 22937, barrel lifter, for reinforced drums 200 litre for zone1, cat. 2G, ex - group IIB, T4



SO M 20094, manual hydraulic jack lift , Load capacity 1000 kg, Lift height 2300 mm, Load bearer for euro pallets and holding clamps for drill cutting heads, for zone 1, cat. 2G, ex-group IIB, T3



SO E 29965, Jack lift with compressed air-operated hydraulics, Load capacity 1000 kg, Lift height 2800 mm, for zone 1, cat. 2G, ex - group IIB, T3



SO E 31000-01, Jack lift with compressed air-operated hydraulics, Load capacity 2000 kg, Lift height 1600 mm, transport of paint buckets ,for zone 2, cat. 2G, ex-group IIA, T3



SO M 20816, Manual jack lift with work platform for zone 2, cat. 2G, ex-group IIB, T4, separate holder on the work platform for valve change, pivotable and height-adjustable



SO M 20815, Lifter with lift arm, 500 kg Load capacity at unloading 1100 mm, 280 kg Load capacity at unloading 2100 mm, for maintenance work. Swivel range ca. 22° right / left, hook height up to 2915 mm for zone 2, cat. 2G, ex-group IIB, T4

Programmable, high frequency Pulse controller

Electric drawbar steering

Powerful three-phase drive transmission 24V 3,0 kW



Fork load width max.1200 mm (manually adjustable)

Mast feeder 1000 mm

Battery on roller conveyer for changing battery on the side

SO E 31121, Reach truck, Load capacity 2000 kg, Lift height 58-2300 mm, for zone 1, cat. 2G, ex - group IIB, T4