

The market requires even more powerful **special equipment** in the future based on **individual problem solutions**.
 We want to meet these requirements using our expertise in combination with our core competences and the Baka efficiency in collaboration with our capable partners.



Wir bauen Stapler nach Maß

mehr als 50.000 Sondergeräte

... über 300 auf

www.bAKA.de

References:

Aleris, Aluplast, Audi, BMW, Bosch, Continental, Corovin, Daimler, Dethleffs Wohnmobile, Deutsche Bundeswehr, Deutz, EADS, EvoBus, Fiege-Engineering, Gaerner, Grässlin, Habisreutinger, Handtmann-Armaturen, Heidelberger-Druck, Hilti, Hoechst, Hörmann Türen, Hüller Hille, INA Schaeffler, ISE Industries, Kaiser + Kraft, Kärcher, Knauf Gips, König & Bauer, Krauss-Maffei, Loher Raumexklusiv, Mahle, MAN, Mercedes Benz Gebrauchtteile-Center, Metabo, MTU, Neumag, Niehoff, nkt cables, Peugeot, Porsche, Renault, Schefenacker, Siemens, Stahl, Viessmann, Volkswagen, Windhoff, ZF

Presented by:



D. Bader Söhne GmbH & Co. KG · Germany

Rathausstraße 37 · D-73630 Remshalden
 Postfach 1320 · D-73626 Remshalden
 Telefon: +49 (0)7151/7006-0
 Telefax: +49 (0)7151/7006-50
 E-mail: Verkauf@baka.de · Internet: www.baka.de

2009/08 Quick Overview Electric four-way side loader



Electric four-way side loader

- Driver seat equipment with two-part floating frame and 4 wheel support
 2000 kg - 10000 kg Load capacity
 Lift height up to 10000 mm
- Driver standing equipment with rigid frame and 3 wheel support
 up to 2500 kg Load capacity and Lift height up to 6500 mm

We build customised forklifts



Y 279, Load capacity 3000 kg up to 6000 mm (load centre distance 800), Cabin, 3 Cameras and monitor



Y 317, Load capacity 7000 kg, Lift height 6000 mm, residual lifting power 6000 kg (load centre distance 600). Fork load width 500-3600 mm, hydraulic pusher forks, headlamp and rear light



Y 302, Load capacity 2000 kg, Lift height 5500 mm, residual lifting power 800 kg (load centre distance 300), Fork load width up to 3050 mm, hydraulic



Y 316, Load capacity 1400 kg (load centre distance 1420), Lift height 3490 mm. Track-guided design for loading curing ovens



Y 320, Load capacity 2500 kg up to Lift height 4000 mm (load centre distance 550), Fork load width up to 1200 mm, hydraulic



Y 322, Load capacity 8000 kg up to Lift height 3500 mm (load centre distance 600), Fork load width 500-3900 mm, hydraulic



Y 293, Load capacity 3500 kg, residual lifting power 1500 kg up to Lift height 6900 mm (load centre distance 1400), Fork load width up to 2500 mm, hydraulic pusher forks



Y 319, Load capacity 4300 kg up to 3300 mm (load centre distance 2000), Fork load width 600 up to 4600 mm, hydraulic pusher forks, Heated cabin, Super-elastic-tyres

fork holder 4100 mm, hydraulically adjustable forks

Hydraulic weighing system

multifunction joystick for hydraulic functions

Side guide rollers adjustable



electronic multidirectional steering

Microprocessor controlled high frequency impulse control

Camera with colour monitor

Vulkollan wheels

Y 311
Load capacity 10000 kg up to Lift height 4000 mm
Load capacity 7000 kg up to Lift height 6500 mm
2 traction drives x 5.0 kW three-phase current