

The market requires even more powerful **special equipment** in the future based on **individual problem solutions**.
We want to meet these requirements using our expertise in combination with our core competences and the Baka efficiency in collaboration with our capable partners.



Wir bauen Stapler nach Maß

mehr als 50.000 Sondergeräte

... über 300 auf

www.bAKA.de

References:

Aleris, Aluplast, Audi, BMW, Bosch, Continental, Corovin, Daimler, Dethleffs Wohnmobile, Deutsche Bundeswehr, Deutz, EADS, EvoBus, Fiege-Engineering, Gaerner, Grässlin, Habisreutinger, Handtmann-Armaturen, Heidelberger-Druck, Hilti, Hoechst, Hörmann Türen, Hüller Hille, INA Schaeffler, ISE Industries, Kaiser + Kraft, Kärcher, Knauf Gips, König & Bauer, Krauss-Maffei, Loher Raumexklusiv, Mahle, MAN, Mercedes Benz Gebrauchtteile-Center, Metabo, MTU, Neumag, Niehoff, nkt cables, Peugeot, Porsche, Renault, Schefenacker, Siemens, Stihl, Viessmann, Volkswagen, Windhoff, ZF

Presented by:



D. Bader Söhne GmbH & Co. KG · Germany

Rathausstraße 37 · D-73630 Remshalden
Postfach 1320 · D-73626 Remshalden
Telefon: +49 (0)7151/7006-0
Telefax: +49 (0)7151/7006-50
E-mail: Verkauf@baka.de · Internet: www.baka.de

2009/08 Quick Overview Electric pallet truck with separate load bearer



Electric pallet truck with separate load bearer

We build customised forklifts

© D. Bader Söhne GmbH & Co. KG, Rathausstr. 37, 73630 Remshalden



SO E 28194, E 38-1000, Load capacity 300 kg, lifting height underside pin 350-1250 mm, load bearer = hydraulic lifting pin with tensioning function



SO E 29283, Load capacity 750 kg, Lift height 50-2500 mm, hydraulic fork pitch +/- 3°, manual tooth adjustment with rod feeder



SO E 30341, E 60-1020B SO, Load capacity 500 kg, Lift height 1510 mm, load bearer with grip and clamp function



SO E 30358, ET 79-1020B, Load capacity 500 kg, load arm unloading 600 mm, Lift height 2810 mm



SO E 29327, E 60-SO, self-supporting with 2 side support teeth, Load capacity 100 kg, Lift height 45-2245 mm, Fork length 1000 mm



SO E 29651, E 38-1020.1, Load arm with rotatable safety load hook, Load capacity 100 kg, Unloading 1190 mm, lifting height hook 100-1100 mm



SO E 30228, E 60-1005B, with load arm and gripper for carrying aluminium casings, Load capacity 50 kg + Gripper, Lift height 130-1810 mm



SO E 29693, E 60-604 SO, with hydraulic tensioning and rotating clamp, Load capacity 100 kg, lifting height centre clamp 280-1790 mm, Clamping range 280-520 mm

manual slide valves for raising/lowering and side slide

Fork carrying width adjustable from 500-1260 mm

towing bar with sensor grip for driving



hydraulic side slide +/- 100 mm left/right

Fork arms with rollers for rotating steel containers

holding arm with tension belts

SO E 30198, E 60-1020B, Load capacity 600 kg, Lift height 1375 mm